

Carbolineum

Wood protection against rotting and attack of termites.
(Line 403)

Description

Carbolineum is a dark brown to black liquid blend of creosote and coal tar and having a typical coal tar odor. For exterior use only.

.....

Product Information

Technical Data

Carbolineum

Vehicle Type	Coal tar distillates
Pigment Type	-
Solids by Volume	-
Theoretical Coverage	7 - 23 m ² / US Gallon
<i>Depending on surface texture and porosity</i>	
Recommended Film Thickness	-
Wet	-
Dry	
Dry Time @ 25°C	-
To Touch	Allow 2 weeks, dries with an oily finish.
To Handle	
To Recoat	No over coating is possible
Dries By	Evaporation
Flash Point	-
Gloss	-
Thin with	No thinning
Clean up Thinner	Thinner #902
Weight Per Gallon	3.90 kg/gallon

Recommended For

Exterior wood protection for above ground, ground contact and below ground uses. Suitable for many applications such as wooden structures, wooden telephone poles, cabins, and posts.

Color

Dark brown.

Applicable by

Brushed or dipped. For above ground applications, apply two coats by brush or dip for 3 minutes per inch of thickness. For ground contact or below ground applications, minimum 5 minutes dip up to 1 hour for further penetration. For fence posts or timber to be buried, dip for 12-48 hours for long-term protection.

Packing

¼ US Gallon (0.945 Liters).

1 US Gallon (3.785 Liters).

5 US Gallon (18.93 Liters).

Clean up

Clean brushes with thinner #902 after use.

Safety Information

Use with adequate ventilation. Avoid contact with eyes and avoid any contact with skin. Wear eye protection and gloves during application. Dispose of contaminated clothes properly.

First Aid

If you experience difficulty in breathing, leave area immediately. In case of eye contact, flush with plenty of water. In case of ingestion, do not induce vomiting. Get medical help immediately.

Remark

All tar-based products are classed as carcinogenic. Carbolineum is toxic and flammable. Always ventilate a working area very well during application in order to remove fumes. The fumes are extremely strong smelling and the smell lingers for a long time. Do not use in direct sunlight. Avoid naked flames in the vicinity. Avoid excessive inhalation and skin contact. Clean hands well before smoking or eating. If material is splashed into the eye, wash well with plenty of clean water and seek medical attention.

Note: Never store treated articles in the vicinity of fish, birds, bees or animals.

.....
Limitation of liability: The information in this data sheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by Pintuco Curacao B.V., whether in technical documentation, or in response to a specific enquiry, or otherwise, are based on data which to the best of our knowledge are reliable. Pintuco Curacao B.V. has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Pintuco Curacao B.V. does therefore not accept any liability arising from loss or injury or damage resulting from such use or the contents of this data sheet (unless there are written agreements stating otherwise). The data contained herein are liable to modification as a result of practical experience and continuous product development. This data sheet replaces and annuls all previous issues and it is the user's responsibility to ensure that this sheet is the current prior to using the product. The English text of this document shall prevail over any translation thereof.

Version: May 2017