

AVF Lakplamuur (Instant Filler)

1 Component acrylic filler/ solvent free.
(Line 403)

Description

AVF Lakplamuur is an all-purpose ready mix filler. AVF Lakplamuur is ideal for quick filling, repairing and smoothing out imperfections on walls, wood and ceilings.

.....

Product Information

Technical Data

AVF Lakplamuur

Vehicle Type	100% Acrylic
Pigment Type	Titanium Dioxide
Solids by Volume	99%
Theoretical Coverage	n/a
<i>Depending on surface texture and porosity</i>	
Recommended Film Thickness/ Dry Time @ 25°C	Fractures < 1mm: less than 10 min. Coat 1-2 mm: 10-15 min. Coat 2-3 mm: 15-20 min
Dries By	Evaporation, coalescence
Flash Point	-
Gloss	n/a
Thin with	n/a
Clean up Thinner	Water
Weight Per Gallon	5.3 kg/gallon

Recommended For

Adheres to stone, stucco, plaster, concrete, polystyrene, wood and MDF.

- can be used immediately
- easy to apply
- sandable
- over paintable
- low shrinkage
- can be used indoors and outdoors.

Color

White.

Applicable by

The filler is applied directly from the bucket with a spreader. Smooth the surface with a wet spreader within 10 minutes.

Packing

Bucket 1 Kg

Clean up

Clean spreader with clean water after use.

Safety Information

Use with adequate ventilation. Avoid contact with eyes and repeated contact with skin. Wear eye protection and gloves during application.

First Aid

If you experience difficulty in breathing, leave area immediately. In case of eye contact, flush with plenty of water. In case of ingestion, do not induce vomiting. Get medical help immediately.

Remark

The surface must be clean, dry and grease free. Stir the bucket thoroughly before use. Patch damaged areas and chalk open joints. If any areas are peeled, cracked or blistered, the condition causing this must be corrected for successful painting. Metal parts such as nail heads, should be wiped clean and primed with the appropriate metal primer. New plasterwork (PH greater than 10) has to cure properly and should be primed with one (1) or two (2) coats of AVF Wall Sealer. If mildew is present remove all traces with a solution of Ammonia. CAUTION: use protective clothing and work goggles when applying Ammonia solution. WARNING! Scraping or sanding of old paint may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS. PREGNANT WOMEN SHOULD AVOID EXPOSURE. New plaster must be allowed to cure (30-60 days).

.....
Limitation of liability: The information in this data sheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by Pintuco Curacao B.V., whether in technical documentation, or in response to a specific enquiry, or otherwise, are based on data which to the best of our knowledge are reliable. Pintuco Curacao B.V. has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Pintuco Curacao B.V. does therefore not accept any liability arising from loss or injury or damage resulting from such use or the contents of this data sheet (unless there are written agreements stating otherwise). The data contained herein are liable to modification as a result of practical experience and continuous product development. This data sheet replaces and annuls all previous issues and it is the user's responsibility to ensure that this sheet is the current prior to using the product. The English text of this document shall prevail over any translation thereof.

Version: May 2017