



AVF Paint Remover/Stripper

(Line 710)

AVF Paint Remover/Stripper has been developed for use in the removal of coatings, varnishes, epoxies and urethanes. The unique surfactant/solvent system allows for rapid penetration and removal of many common coatings. Does not contain Methylene Chloride

Description

AVF Paint Remover/Stripper is a Non-Methylene Chloride, alternative to methylene chloride, toluene, benzene -based paint removers/strippers. This product effectively replaces methylene chloride, toluene, benzene and other hazardous solvents traditionally used for paint clean up and paint removal. Effective on acrylics, lacquers, polyurethanes, and epoxies. Applicable on all types of wood and metal (except aluminum). When stripping of natural wood, no discolorations occurs. Plastics will be affected in general. It is recommended to test beforehand with plastic surface in an inconspicuous place. AVF Paint Remover/Stripper will remove multiple layers of paint in 2-4 hours. AVF Paint Remover/Stripper works best when covered with paper to prevent evaporation from taking place.

.....

Product Information

Technical Data

Flash Point

Color

Odor

Thin with

Clean up Thinner

Weight Per Gallon

AVF Paint Remover

270°C

Clear, colorless liquid

Characteristic

Max 2% by volume when removing emulsion paint

Hot Water

3.77 Kg/Gal

Recommended For

Effective on all coatings, even two step high-solids epoxy and polyurethane resins. AVF Paint Remover/Stripper is an excellent paint gun cleaner. Reaction time varies with the paint or coating to be removed.

Color

Clear gel.

Applicable by

Apply AVF Paint Remover/Stripper with a brush, roller or a spatula in a thick layer. Before use, always carry out a test on a small area first. When using a brush, we recommend a brush with natural bristles. Some synthetic brushes are affected by AVF Paint Remover/Stripper. Nylon, however, is not affected.

Packing

¼ US Gallon (0.945 Liters).
1 US Gallon (3.785 Liters).

Clean up

Clean brushes and rollers with hot water (60 °C – 90°C) after use.

Safety Information

Use with adequate ventilation. Avoid contact with eyes and repeated contact with skin. Wear eye protection and gloves during application.

First Aid

If you experience difficulty in breathing, leave area immediately. In case of eye contact, flush with plenty of water. In case of ingestion, do not induce vomiting. Get medical help immediately.

Remark

Carry out a test on a small area first. Apply a thick layer of paint remover with a soft brush. After 15-45 minutes depending on the type of paint and the thickness of the paint, it can take up to several hours. Repeat if necessary, treatment. Dissolved paint can be removed with a scraper, a brush or a high-pressure sprayer (60-90 ° C). Surface thoroughly rinse with water. It is of great importance (for outside walls) to start at the bottom and work upwards. Intense sunlight and strong winds can cause the stripper dries too quickly. In these cases, apply more stripper on the dried pieces.

.....
Limitation of liability: The information in this data sheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by Pintuco Curacao B.V., whether in technical documentation, or in response to a specific enquiry, or otherwise, are based on data which to the best of our knowledge are reliable. Pintuco Curacao B.V. has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Pintuco Curacao B.V. does therefore not accept any liability arising from loss or injury or damage resulting from such use or the contents of this data sheet (unless there are written agreements stating otherwise). The data contained herein are liable to modification as a result of practical experience and continuous product development. This data sheet replaces and annuls all previous issues and it is the user's responsibility to ensure that this sheet is the current prior to using the product. The English text of this document shall prevail over any translation thereof.