

Thinner #995 (Xylene) (Line 309)

Description

Thinner #995 can be used in place of thinner #990 to thin specified oil-based paint, lacquer and varnish when a slower rate of evaporation is desired. Thinner #995 will also remove certain adhesives, and is an excellent clean-up solvent for tools and equipment immediately after use.

Product Information

<u>Technical Data</u>	<u>Thinner #995</u>
Flash Point	27°C
Density (g/cm ³)	0.87
Color	Clear, colorless liquid
Odor	Sweet, balsam-like odor
Risk phrases	R10 R20 R22 R36 R37 R38
Safety phrases	S25

Recommended For

Paint thinner for polyester and epoxy resins.

Packing

¼ US Gallon (0.945 Liters).
1 US Gallon (3.785 Liters).
5 US Gallon (18.92 Liters).

Safety Information

Use with adequate ventilation. Avoid contact with eyes and repeated contact with skin. Wear eye protection and gloves during application. If health, safety and environmental information is required a Health and Safety Data Sheet can be obtained from AVF Paints (Pintuco Curacao B.V.).

First Aid

If you experience difficulty in breathing, leave area immediately. In case of eye contact, flush with plenty of water. In case of ingestion, do not induce vomiting. Get medical help immediately.

Limitation of liability: The information in this data sheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by Pintuco Curacao B.V., whether in technical documentation, or in response to a specific enquiry, or otherwise, are based on data which to the best of our knowledge are reliable. Pintuco Curacao B.V. has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Pintuco Curacao B.V. does therefore not accept any liability arising from loss or injury or damage resulting from such use or the contents of this data sheet (unless there are written agreements stating otherwise). The data contained herein are liable to modification as a result of practical experience and continuous product development. This data sheet replaces and annuls all previous issues and it is the user's responsibility to ensure that this sheet is the current prior to using the product. The English text of this document shall prevail over any translation thereof.