



AVF Acrylic Road Marking Paint

AVF Acrylic Road Marking Paint is a single component, quick drying, high build, modified acrylic road & line marking paint.
(Line 331)

Description

AVF Acrylic Road Marking Paint is a fast-dry solvent based paint containing rutile titanium dioxide and silicate pigmentation. AVF Acrylic Road Marking Paint dries fast and hence traffic hold up is minimum. AVF Acrylic Road Marking Paint can be applied over asphalt, concrete surfaces and tar sealed substrates. Excellent reflective properties with the addition of glass beads.

Product Information

Technical Data

AVF Acrylic Road Marking Paint

Vehicle Type	Acrylic Resin
Pigment Type	Titanium Dioxide
Solids by Volume	51 – 53 %
Theoretical Coverage	8.5 m ² /US Gallon @215µm DFT
<i>Depending on surface texture and porosity</i>	
Recommended Film Thickness	
Wet	410µm
Dry	215µm
Dry Time @ 25°C	
To Touch	15 Minutes
To Handle	1 Hours
To Recoat	12 Hours
Dries By	Oxidation
Flash Point	-
Gloss	Flat or Reflective
Thin with	Thinner #995 (for airless spray max 3% by volume)
Clean up Thinner	Thinner #995
Weight Per Gallon	5.51 kg/gallon

Recommended For

Asphalt and concrete. For reflective properties, glass beads should be sprinkled into the wet coat 420gr/m². The beads should be DROP ON STANDAR (code: 331K50010, bags of 25Kg) .

**Color**

White/Yellow/Black.

Applicable by

Brush, roller or airless spray.

Packing

1 US Gallon (3.785 Liters).

5 US Gallon (18.93 Liters).

Clean up

Clean brushes and rollers with Thinner #995 or Thinner #308 after use.

Safety Information

Use with adequate ventilation. Avoid contact with eyes and repeated contact with skin. Wear eye protection and gloves during application.

First Aid

If you experience difficulty in breathing, leave area immediately. In case of eye contact, flush with plenty of water. In case of ingestion, do not induce vomiting. Get medical help immediately.

Remark

The surface to be coated must be clean, free from dirt, dust, oil and grease etc. Apply Road Marking Paint and leave to dry for as long as is practically possible. It must be noted that the longer the paint is allowed to dry and the rougher the surface to be coated, the longer the paint will last. The paint will be touch dry within +3-5 minutes. This product can be applied directly to all clean, new or previously painted surfaces. **WARNING! Scraping or sanding of old paint may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS. PREGNANT WOMEN SHOULD AVOID EXPOSURE.**

.....
Limitation of liability: The information in this data sheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by Pintuco Curacao B.V., whether in technical documentation, or in response to a specific enquiry, or otherwise, are based on data which to the best of our knowledge are reliable. Pintuco Curacao B.V. has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Pintuco Curacao B.V. does therefore not accept any liability arising from loss or injury or damage resulting from such use or the contents of this data sheet (unless there are written agreements stating otherwise). The data contained herein are liable to modification as a result of practical experience and continuous product development. This data sheet replaces and annuls all previous issues and it is the user's responsibility to ensure that this sheet is the current prior to using the product. The English text of this document shall prevail over any translation thereof.