

## AVF Roof Paint

**Long lasting premium quality latex paint.**  
(Line 207)

### Description

AVF Roof Paint is a long lasting premium quality latex paint. AVF Roof Paint is very easily applied with brush, roller or airless spray. AVF Roof Paint has a low luster finish and is ideally suitable for the decoration of new or old roofs, cement tile and asbestos cement sheets.

### Product Information

#### Technical Data

#### AVF Roof Paint

Vehicle Type	Acrylic Copolymer Latex
Pigment Type	Titanium Dioxide
Solids by Volume	42%
Theoretical Coverage	44 m <sup>2</sup> /US Gallon @ 35µm DFT
<i>Depending on surface texture and porosity</i>	
Recommended Film Thickness	
Wet	84/90µm
Dry	35/38µm
Dry Time @ 25°C	
To Touch	½Hours
To Handle	2 Hours
To Recoat	4 hours
Dries By	Evaporation
Flash Point	-
Gloss	Satin
Thin with	Water (max 5% by volume to be added)
Clean up Thinner	Water
Weight Per Gallon	5.15 kg/gallon

### Recommended For

Asbestos cement sheets, roofing tiles

Note: New asbestos cement sheets should be pre-treated with AVF Wall Sealer (solvent based), followed by two (2) coats of AVF Roof Paint.

### Color

Color card shades, Special Colors upon request.

### **Applicable by**

Brush, roller or airless spray.

### **Packing**

1 US Gallon (3.785 Liters)

### **Clean up**

Clean brushes and rollers with clean water after use.

### **Safety Information**

Use with adequate ventilation. Avoid contact with eyes and repeated contact with skin. Wear eye protection and gloves during application.

### **First Aid**

If you experience difficulty in breathing, leave area immediately. In case of eye contact, flush with plenty of water. In case of ingestion, do not induce vomiting. Get medical help immediately.

### **Remark**

Surface must be clean, free of loose paint, chalk, grease and dust. Patch damaged areas and chalk open joints. If any areas are peeled, cracked or blistered, the condition causing this must be corrected for successful painting. Metal parts such as nail heads, should be wiped clean and primed with the appropriate metal primer. New plasterwork (PH greater than 10) has to cure properly and should be primed with one (1) or two (2) coats of AVF Wall Sealer. If mildew is present remove all traces with a solution of Ammonia. CAUTION: use protective clothing and work goggles when applying Ammonia solution. WARNING! Scraping or sanding of old paint may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS. PREGNANT WOMEN SHOULD AVOID EXPOSURE. New plaster must be allowed to cure (30-60 days).

.....  
**Limitation of liability:** The information in this data sheet is based upon laboratory tests we believe to be accurate and is intended for guidance only. All recommendations or suggestions relating to the use of the products made by Pintuco Curacao B.V., whether in technical documentation, or in response to a specific enquiry, or otherwise, are based on data which to the best of our knowledge are reliable. Pintuco Curacao B.V. has no control over either the quality or condition of the substrate, or the many factors affecting the use and application of the product. Pintuco Curacao B.V. does therefore not accept any liability arising from loss or injury or damage resulting from such use or the contents of this data sheet (unless there are written agreements stating otherwise). The data contained herein are liable to modification as a result of practical experience and continuous product development. This data sheet replaces and annuls all previous issues and it is the user's responsibility to ensure that this sheet is the current prior to using the product. The English text of this document shall prevail over any translation thereof.